

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/541570



(43) International Publication Date
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number
WO 2004/062946 A1

(51) International Patent Classification⁷: B60B 7/20

[GB/GB]; Farmhouse Flat 2, Wallange Paddocks, Coal Pit Lane, Stanthorne, Middlewich CW10 0NB (GB).

(21) International Application Number:
PCT/GB2004/000030

(74) Agents: DOWNEY, William, Gerrard et al.; Wilson Gunn M'caw, 5th Floor, Blackfriars House, The Parsonage, Manchester, M3 2JA (GB).

(22) International Filing Date: 8 January 2004 (08.01.2004)

(25) Filing Language: English

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English

(30) Priority Data:
0300553.5 10 January 2003 (10.01.2003) GB

(71) Applicant (for all designated States except US): BENTLEY MOTORS LIMITED [GB/GB]; Pym's Lane, Crewe, Cheshire CW1 3PL (GB).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),


(72) Inventor; and

(75) Inventor/Applicant (for US only): CANNON, Shane

[Continued on next page]

(54) Title: APPARATUS FOR MAINTAINING THE ORIENTATION OF A BADGE OR OTHER INSIGNIA

(57) Abstract: Apparatus for maintaining the orientation of a badge 6 comprises a housing (1) which is a snap fit in a vehicle wheel (2). The badge 6 is mounted on a support (7) which comprises an axle (8) mounted on bearings (4) and (5) and a counterweight (9). The counterweight creates an off axis centre of gravity which provides a force to maintain the correct orientation of the badge. Movement is damped to prevent excessive oscillation. Damping may be frictional, fluid, air or magnetic. In a modification a centrifugal clutch may be provided to restrain oscillation. In a further modification the position of the badge may be electronically controlled.



WO 2004/062946 A1